

OZONE DESTRUCT MODULE

DM25 - DM50 - DM75 - DM100
DEXF7 2.0

Primozone[®]
REDEFINING OZONE TECHNOLOGY



ENERGY EFFICIENT

Removal of unreacted ozone.



EASY TO INSTALL

Plug & Play

LOW MAINTENANCE

Requires only general safety inspection.

MODERN.
INTELLIGENT.



TECHNICAL SPECIFICATIONS

MODEL	OZONE OUTPUT	FLOW m ³ /h	OPERATING TEMPERATURE	MAX POWER (kW)	CONNECTIONS IN/OUT	VOLTAGE	LENGTH x WIDTH x HEIGHT	WEIGHT
DM25	< 0.1 ppm	25	50 - 60 °C 122 - 140 °F	0.9	DN100 PN6	400 V+N+PE	1123 x 755 x 989 mm 44.2 x 29.7 x 38.9 in	300 kg 661 lbs
DM50	< 0.1 ppm	50	50 - 60 °C 122 - 140 °F	1.4	DN100 PN6	400 V+N+PE	1123 x 755 x 989 mm 44.2 x 29.7 x 38.9 in	330 kg 728 lbs
DM75	< 0.1 ppm	75	50 - 60 °C 122 - 140 °F	3.5	DN100 PN6	400 V+N+PE	1123 x 755 x 989 mm 44.2 x 29.7 x 38.9 in	400 kg 882 lbs
DM100	< 0.1 ppm	100	50 - 60 °C 122 - 140 °F	3.8	DN100 PN6	400 V+N+PE	1123 x 755 x 989 mm 44.2 x 29.7 x 38.9 in	430 kg 948 lbs
DEXF7 2.0	< 0.1 ppm	7	50 - 60 °C 122 - 140 °F	0.54	DN65	400 V+N+PE	Height 620 mm / 24 mm Radius 100 mm / 4 in	15 kg 33 lbs

t